

HOLGATE[®] TOYS

America's Wooden Toy Maker Since 1929

CERTIFICATE OF COMPLIANCE

We certify that any and all products supplied where applicable, are now, and will be in the future, in compliance with all regulations specified within The Consumer Product Safety Improvement Act of 2008 including:

ASTM F963-07

Small Parts Warnings

Lead Content (15 U.S.C. 2052(a) (16))

Phthalates Restrictions (sec. 108)

3rd Party Independent Testing (14(a)(15 U.S.C. 2063(a))

Testing shall be made available upon request by contacting:

Company Name: Pepperell Braiding Company, Inc.
dba Holgate Toy Company
548 High Street
Bradford, PA 16701
info@holgatetoy.com

=====**Division of Pepperell Braiding Company**=====

P.O. Box 528 • 548 High Street • Bradford, PA 16701 • 814-368-4454 • Fax 814-368-9140

ACTS TESTING LABS, INC.

25 Anderson Road • Buffalo, N.Y. 14225-4906 • Tel: (716) 897-3300 • Fax: (716) 897-0876

TECHNICAL REPORT 9B-2350

April 24, 1989

Page 1 of 3

Mr. Richard Bly
President
HOLGATE TOY COMPANY

SUBJECT:

Evaluation of 12 samples received on March 29, 1989.

INTRODUCTION:


The samples were evaluated according to the Federal Hazardous Substances Act (FHSA), Title 16, Code of Federal Regulations (CFR), Part 1500 ff. and ASTM F963-86, "Standard Consumer Safety Specification on Toy Safety".

Sample Description:	BINGO BED
Vendor:	Not Listed
Model/Style:	1082
Origin:	USA
P.O. No.:	n / a

EXECUTIVE SUMMARY:


The samples MEET the requirements of the Federal Hazardous Substances Act, Title 16, Code of Federal Regulations, Part 1500 ff. and ASTM F963-86, "Standard Consumer Safety Specification on Toy Safety".

ACTS TESTING LABS, INC.



Robert M. Hochulski
Supervisor, Toy Laboratory

ACTS TESTING LABS, INC.



Tina M. Goerss
Sr. Technician, Toy Laboratory

mas

Mr. Richard Bly
HOLGATE TOY COMPANY

April 24, 1989
TECHNICAL REPORT 9B-2350
Page 2 of 3

I) RESULTS:

A) AGE GRADING (ASTM F963-86, Section 5.6)

The samples do not contain an age grade, however according to the clients catalog the samples will be age graded for children 18 months and over which is appropriate according to the age grading guidelines of the CPSC and ASTM Toy Standard F963-86.

B) USE AND ABUSE TESTS

1. Impact Test (FHSA, Section 1500.53(b))

Samples A and B were dropped four times from a height of 3.0 feet onto the specified impact surface in the assembled state. No Small Objects, Sharp Edges nor Sharp Points were revealed.

The individual components of samples C and D were dropped four times at a height of 3.0 feet onto the specified impact surface. No Small Objects, Sharp Edges nor Sharp Points were revealed.

2. Torque Test (FHSA, Section 1500.53(e))

All graspable components of samples E, F, G, and H were subjected to 4 inch-pounds of torque for ten seconds in a clockwise and counterclockwise direction. No Small Objects, Sharp Edges, nor Sharp Points were revealed.

3. Tension Test (FHSA, Section 1500.53(f))

All graspable components of samples E, F, G, and H were subjected to 15 pounds of tension for ten seconds in a parallel and perpendicular direction using a calibrated tension gauge. No Small Objects, Sharp Edges, nor Sharp Points were revealed.

4. Compression Test (FHSA, Section 1500.53(g))

Samples I, J, K, and L were subjected to 30 pounds of compression for ten seconds on all areas that were inaccessible to flat surface contact during the Impact Test. No Small Objects, Sharp Edges, nor Sharp Points were revealed.

Mr. Richard Bly
HOLGATE TOY COMPANY

April 24, 1989
TECHNICAL REPORT 9B-2350
Page 3 of 3

I) RESULTS:

D) FLAMMABILITY (FHSA, Section 1500.3(c)(6)(vi))

The samples were subjected to a five second application of the test flame as specified in Section 1500.44 of the FHSA. The colored pegs exhibited ignition within the five second application of the test flame. The average burn rate of the colored pegs was determined to be 0.01 inch per second, which MEET the requirement of Section 1500.3(c)(6)(vi) of a burn rate no greater than 0.1 inch per second.

E) WOOD (ASTM F963-86, Section 4.8.3)

The samples were evaluated for the presence of splinters on all accessible surfaces. This Section requires that all accessible surfaces and edges of wood shall be free of splinters.

No splinters were revealed before or after specified abuse testing.