

HOLGATE[®] TOYS

America's Wooden Toy Maker Since 1929

CERTIFICATE OF COMPLIANCE

We certify that any and all products supplied where applicable, are now, and will be in the future, in compliance with all regulations specified within The Consumer Product Safety Improvement Act of 2008 including:

ASTM F963-07

Small Parts Warnings

Lead Content (15 U.S.C. 2052(a) (16))

Phthalates Restrictions (sec. 108)

3rd Party Independent Testing (14(a)(15 U.S.C. 2063(a))

Testing shall be made available upon request by contacting:

Company Name: Pepperell Braiding Company, Inc.
dba Holgate Toy Company
548 High Street
Bradford, PA 16701
info@holgatetoy.com

=====**Division of Pepperell Braiding Company**=====

P.O. Box 528 • 548 High Street • Bradford, PA 16701 • 814-368-4454 • Fax 814-368-9140

ACTS TESTING LABS, INC.

25 Anderson Road • Buffalo, N.Y. 14225-4906 • Tel: (716) 897-3300 • Fax: (716) 897-0876

TECHNICAL REPORT 9B-2332

April 21, 1989
Page 1 of 3

Mr. Richard Bly
President
HOLGATE TOY COMPANY

SUBJECT:

Evaluation of 12 samples received on March 29, 1989.

INTRODUCTION:


The samples were evaluated according to the Federal Hazardous Substances Act (FHSA), Title 16, Code of Federal Regulations (CFR), Part 1500 ff. and ASTM F963-86, "Standard Consumer Safety Specification on Toy Safety".

Sample Description:	ROCKY COLOR CONE
Vendor:	Not Listed
Model/Style:	1107
Origin:	USA
P.O. No.:	n / a

EXECUTIVE SUMMARY:


The samples MEET the requirements of the Federal Hazardous Substances Act, Title 16, Code of Federal Regulations, Part 1500 ff. and ASTM F963-86, "Standard Consumer Safety Specification on Toy Safety".

ACTS TESTING LABS, INC.



Robert M. Hochulski
Supervisor, Toy Laboratory

ACTS TESTING LABS, INC.



Tina M. Goerss
Sr. Technician, Toy Laboratory

mas

I) RESULTS:

A) AGE GRADING (ASTM F963-86, Section 5.6)

The samples do not contain an age grade, however according to the clients catalog the samples will be age graded for children 12 months and over which is appropriate according to the age grading guidelines of the CPSC and ASTM Toy Standard F963-86.

B) USE AND ABUSE TESTS

1. Impact Test (FHSA, Section 1500.51(b))

Samples A and B were dropped ten times from a height of 4.5 feet onto the specified impact surface in the assembled state. Although, no Small Objects, Sharp Edges nor Sharp Points were revealed the center peg of sample A was released during the sixth drop.

The individual components of samples C and D were dropped ten times at a height of 4.5 feet onto the specified impact surface. No Small Objects, Sharp Edges nor Sharp Points were revealed.

2. Torque Test (FHSA, Section 1500.53(e))

All graspable components of samples E, F, G, and H were subjected to 4 inch-pounds of torque for ten seconds in a clockwise and counterclockwise direction. No Small Objects, Sharp Edges, nor Sharp Points were revealed.

3. Tension Test (FHSA, Section 1500.53(f))

All graspable components of samples E, F, G, and H were subjected to 15 pounds of tension for ten seconds in a parallel and perpendicular direction using a calibrated tension gauge. No Small Objects, Sharp Edges, nor Sharp Points were revealed.

4. Compression Test (FHSA, Section 1500.53(g))

Samples I, J, K, and L were subjected to 30 pounds of compression for ten seconds on all areas that were inaccessible to flat surface contact during the Impact Test. No Small Objects, Sharp Edges, nor Sharp Points were revealed.

Mr. Richard Bly
President
HOLGATE TOY COMPANY

June 14, 1990
TECHNICAL REPORT 0B-7580
Page 3 of 3

I) **RESULTS:**

D) **PULL TOYS (ASTM F963-86, Section 4.13.2)**

This Section addresses potential entanglement and strangulation hazards associated with pull cords. The Section requires that the pull cord of toys intended for children under 36 months of age measuring over 12 inches in length must not have beads or any other attachments which could tangle to form a loop.

The pull cords of the revised production samples were evaluated for proper length and design. The pull cords were determined to be 18 inches long. The pull cord does not contain knots, beads or any other attachments. The samples MEET the requirement of this Section.